



# Dell PowerEdge M710HD

The Dell™ PowerEdge™ M710HD blade server helps you run business applications efficiently, reduce your data center footprint, ease data management and trim system maintenance time.

The M710HD is a data center virtualization-optimized blade that offers tremendous IO throughput, maximized memory density, and robust optional Intel® Xeon® 5600 processing power, all in an ultra-dense form factor with enterprise-class high availability. The M710HD is the first Dell M-Series server with a flexible network daughtercard (NDC) designed to allow for future integrated connectivity options.

## Rack-dense performance

Unleash the power of massive IO throughput, core-rich Intel Xeon processors and an abundance of DD3 DIMMs on your toughest data center workloads. With massive I/O throughput, powerful multi-core processing and ultra-high-density memory options, the PowerEdge M710HD blade server can let you flex your data center muscles while taking on the toughest workloads. Flexible and robust IO deployment is achievable through multiple iSCSI, Ethernet, FibreChannel and InfiniBand options with additional future integrated network connectivity through the network daughtercard (NDC). Processing power from up to 12 Intel Xeon 5600 series cores and maximized RAM density with 18 DIMM slots allows for condensed full-height blade horsepower and cost-efficient DDR3 memory scaling in an ultra-dense form factor.

## Efficiency without compromise

Increase your capability to deploy virtualized solutions that can reduce power consumption while increasing performance capacity. The expanded addressable memory in the PowerEdge M710HD allows you to utilize more virtual machines from your existing hypervisor licensing, helping you save money and increase your virtualized deployments using existing resources. Optimized airflow design coupled with high-efficiency fans and power supplies enable the Dell M1000e blade enclosure to effectively power and cool PowerEdge M710HD servers while helping to reduce overall power draw. This allows you to reclaim power for use elsewhere in your data center, save on operational costs, and help the environment.

## Enterprise-class reliability and management

Spend more time on your business and less on maintaining your IT with embedded system management features on the PowerEdge M710HD and the Chassis Management Controller (CMC). The PowerEdge M710HD blade server is designed to ease your mind and reduce your operating costs delivering the closest thing to a worry-free data

center. Optional failsafe embedded hypervisors and HDD fault tolerance through a hardware RAID controller offer protective redundancy that safeguards your organization's data from loss or corruption. Simplified systems management is achieved through automated discovery which automates configuration of new hardware and enables pre-provisioning of LAN/SAN resources.

In addition, one-to-many updating through the CMC and Virtual File Share simplifies the update process for BIOS, firmware and drivers without additional software. Proactive management provides immediate access to system status, issues and alerts through a single, easy-to-use interface that includes one-click key functions to help quickly resolve issues.

## Dell Services

Dell Services can help reduce IT complexity, lower costs, and eliminate inefficiencies by making IT and business solutions work harder for you. The Dell Services team takes a holistic view of your needs and designs solutions for your environment and business objectives while leveraging proven delivery methods, local talent, and in-depth domain knowledge for the lowest TCO.

Designed for enterprise database and virtualization deployments, the PowerEdge M710HD features tremendous I/O throughput, maximized memory density and robust processing power.

Feature	PowerEdge M710HD technical specification	
<b>Processors</b>	Quad-core or six-core Intel® Xeon® processors 5500 and 5600 series	
<b>Chipset</b>	Intel 5520	
<b>Memory<sup>1</sup></b>	Up to 288GB (18 DIMM slots): 1GB/2GB/4GB/8GB/16GB ECC DDR3 up to 1333MT/s	
<b>Drive bays</b>	Two 2.5" SAS/Solid State hot-pluggable drives	
<b>Storage</b>	<b>Hot-plug hard drive options:</b> 2.5" SATA SSD, SAS (15K, 10K) <b>External storage:</b> For information about Dell external storage options, visit <a href="http://Dell.com/Storage">Dell.com/Storage</a> .	
<b>RAID controller options</b>	PERC H200 Integrated SAS Controller (6Gb/s)	
<b>I/O mezzanine card options</b>	<b>Fully populated mezzanine card slots and switch modules will yield 3 redundant I/O fabrics per blade.</b> <b>1Gb and 10Gb Ethernet:</b> Broadcom® Dual-Port 1Gb Ethernet with TOE (BCM-5709S) Intel Quad-Port 1Gb Ethernet Broadcom Quad-Port 1Gb Ethernet (BCM-5709S) Intel Dual-Port 10Gb Ethernet Broadcom Dual-Port 10Gb Ethernet (BCM-57711) <b>InfiniBand:</b> Mellanox® ConnectX®-2 Dual-Port Dual Data Rate (DDR) and Quad Data Rate (QDR) InfiniBand <b>Fibre Channel:</b> QLogic Dual-Port FC8 Fibre Channel Host Bus Adapter (HBA) (QME2572) Emulex Dual-Port FC8 Fibre Channel HBA (LPe1205-M) Emulex 8 or 4 Gb/s Fibre Channel Pass-Through Module	<b>10Gb Enhanced Ethernet and Converged Network Adapters (CEE/DCB/FCoE):</b> Intel Dual-Port 10Gb Enhanced Ethernet (FCoE Ready for Future Enablement) Emulex® Dual-Port CNA (OCM10102-F-M)—supports CEE/DCB 10GbE + FCoE QLogic® Dual-Port CNA (QME8142)—supports CEE/DCB 10GbE + FCoE QLogic Dual-Port CNA (QME8242-k)—supports 10GbE + NPAR Brocade® BR1741M-k Dual-Port Mezzanine CNA Broadcom 57712-k Dual-Port Converged Network Daughter Card (NDC)—supports CEE/DCB 10GbE + NPAR + FCoE + iSCSI-TLV
<b>Communications</b>	Two embedded Broadcom NetXtreme® II 5709 Gigabit Ethernet NICs with failover and load balancing. TOE (TCP/IP Offload Engine) supported on Microsoft® Windows Server® 2003 SP1 or higher with Scalable Networking Pack. iSCSI Offload supported on Windows Server 2003 SP1 or higher, Red Hat® Enterprise Linux® 5, and Novell® SUSE® Linux Enterprise Server 10. Scalable Networking Pack for Windows Server 2003 is not required. Boot from SAN (iSCSI and FC) supported Optional add-in NICs: See I/O Mezzanine Card Options Optional add-in HBAs: See I/O Mezzanine Card Options	
<b>Communications options</b>	Four embedded Broadcom 5709S Gigabit NIC with failover and load balancing. TOE (TCP/IP Offload Engine) supported on Microsoft Windows Server 2003 SP1 or higher with Scalable Networking Pack. iSCSI Offload supported on Windows Server 2003 SP1 or higher, Red Hat Enterprise Linux 5, and SUSE Linux Enterprise Server 10. Scalable Networking Pack for Windows Server 2003 is not required. Boot from SAN (iSCSI and FC) supported Optional add-in NICs: See I/O Mezzanine Card Options Optional add-in HBAs: See I/O Mezzanine Card Options	
<b>Operating systems</b>	Microsoft Windows Server 2012 Microsoft Windows Server 2012 Essentials Microsoft Windows Server 2008 SP2, x86/x64 (x64 includes Hyper-V®) Microsoft Windows Server 2008 R2 SP1, x64 (includes Hyper-V v2) Microsoft Windows® HPC Server 2008 Novell® SUSE® Linux Enterprise Server Red Hat Enterprise Linux Oracle® Solaris™ <b>Virtualization options:</b> Citrix® XenServer® Microsoft Hyper-V through Microsoft Windows Server 2008 VMware® vSphere® ESX™ and ESXi™ Red Hat Enterprise Virtualization® For more information on the specific versions and additions, visit <a href="http://Dell.com/OSsupport">Dell.com/OSsupport</a> .	
<b>Featured database applications</b>	Microsoft SQL Server solutions (see <a href="http://Dell.com/SQL">Dell.com/SQL</a> ) Oracle database solutions (see <a href="http://Dell.com/Oracle">Dell.com/Oracle</a> )	
<b>Management options</b>	<b>Dell™ OpenManage™ software tools</b> Integration with third-party management solutions through the Dell Certified Partner Program <b>Altiris™ Deployment Solution for Dell blade servers</b> Designed to help reduce deployment time from hours to minutes	<b>Integrated Dell Remote Access Controller (iDRAC)</b> Out-of-band alerting, status, inventory, and troubleshooting through Secure Web GUI/CLI (telnet/SSH) <b>Console redirection</b> vMedia (virtual media)—Map optical or hard drives to the blade from remote workstations over a network vKVM (virtual KVM) out-of-band remote console redirection—supports Java or ActiveX plug-ins IPMI 2.0 support
<b>Power supply</b>	Supplied by Dell PowerEdge™ M1000e Blade Chassis	
<b>Video</b>	Integrated Matrox® G200 with 8MB memory	
<b>Systems management</b>	Dell OpenManage BMC, IPMI 2.0 compliant Unified Server Configurator	Lifecycle Controller iDRAC6 Enterprise with optional vFlash media

For more information about the Dell blade solution, see the [PowerEdge M1000e Technical Guide](#) or the [M1000e Blade Chassis Specification Sheet](#).

<sup>1</sup> GB means 1 billion bytes and TB equals 1 trillion bytes; actual capacity varies with preloaded material and operating environment and will be less.

Learn more at [Dell.com/Blades](http://Dell.com/Blades)

© 2012 Dell Inc. All rights reserved. Dell, the DELL logo, the DELL badge, PowerEdge, and OpenManage are trademarks of Dell Inc. Other trademarks and trade names may be used in this document to refer to either the entities claiming the marks and names or their products. Dell disclaims proprietary interest in the marks and names of others. This document is for informational purposes only. Dell reserves the right to make changes without further notice to any products herein. The content provided is as is and without express or implied warranties of any kind.

